

- 8 earth-toned colors
- Stone-look exudes a feeling of rustic elegance
- Ideal for all types of commercial and residential applications


- Cost-effective and environmentally responsible
- Contributes to the efforts of companies seeking LEED certification of new buildings and major renovations



EC114 Grand Canyon




EC101 Wetlands




EC102 Marshland




EC103 Earth



EC116 Plymouth Rock



EC104 Pine Barren



EC105 Night Air



EC001 Storm  
8" x 8" Cross-Sheen 8" x 8" Cross-Tread

### Sizes Available

Nominal	Size Actual	Thickness
8" x 8"	7-3/4" x 7-3/4"	5/16"
12" x 12"	11-3/4" x 11-3/4"	5/16"

\*EC001 only

### Trim Sizes

Nominal Size	Actual Size	Thickness
4" x 12" Single Bullnose	3-3/4" x 11-3/4"	5/16"
6" x 12" Cove Base	5-7/8" x 11-3/4"	5/16"




4" x 12" Single Bullnose



6" x 12" Universal Cove Base

### Trim Sizes (EC001 only)


Nominal Size	Actual Size	Thickness
6" x 8" Cove Base	5-7/8" x 7-3/4"	5/16"
6" x 8" Cove Base Corner Left	5-7/8" x 7-3/4"	5/16"
6" x 8" Cove Base Corner Right	5-7/8" x 7-3/4"	5/16"
1" x 6" Cove Base Inside Corner	1" x 5-7/8"	-
1" x 6" Cove Base Outside Corner	1" x 5-7/8"	-



6" x 8" Cove Base



6" x 8" Cove Base Corner Left



6" x 8" Cove Base Corner Right



Inside & Outside Base Corner

### Recommended Usage

EcoCycle is recommended for interior floors and walls and exterior walls in both commercial and residential applications. EcoCycle is not recommended for exterior horizontal use, with the exception of EC001 in the Cross-Tread finish, which is suitable for exterior horizontal surfaces and paving.

### Shade & Texture Index

EcoCycle has a shade variation of V3. EcoCycle EC001 has a shade variation of V1



V1



V2



V3



V4

V1=Uniform Appearance  
V2=Slight Variation  
V3=Moderate Variation  
V4=Substantial Variation

### Care and Maintenance

Regular cleaning is the best way to keep EcoCycle tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville products is available at [www.crossvilleinc.com](http://www.crossvilleinc.com).

### Product Performance

	EcoCycle	EC001 (CTS only)	
Breaking Strength	>350-420 lbf.	>350-420 lbf.	ASTM C648
Bond Strength	>200 psi	>200 psi	ASTM C482
Chemical Resistance	Unaffected	Unaffected	ASTM C650
Frost Resistance	Resistant	Resistant	ASTM C1026
Water Absorption	<10%	<10%	ASTM C373
Scratch Hardness	7	6	MOH's Scale
COF-Dry	>0.8	>0.8	ASTM C1028
COF-Wet	>0.6	>0.8	ASTM C1028





EcoCycle  
Floor – EC101 Wetlands 12" x 12", EC102 Marshland 12" x 12",  
EC104 Pine Barren 12" x 12"

Crossville, Inc. • P.O. Box 1168, Crossville TN 38557  
Phone: 931.484.2110 • Fax: 931.456.2956  
E-mail: [crossc@crossvilleinc.com](mailto:crossc@crossvilleinc.com) • [www.crossvilleinc.com](http://www.crossvilleinc.com)

 CROSSVILLE.