


UltiMetal

PORCELAIN STONE


- UltiMetal offers the luxe appeal of metal with the legendary durability of Crossville's Porcelain Stone.
- Create a minimalist design scheme with large expanses of field tile.
- The metallic micromesh adds texture and subtle shine.

- Boldly patterned mosaics and listellos.
- Large format, rectified sizes with the look of metal in five in-demand colors.


Field Tile Available in 24" x 24", 12" x 24", 6" x 24", 12" x 12"




MTL01 White




MTL03 Grey



MTL04 Copper



MTL02 Silver




MTL05 Black


Listellos



12" x 24" MTLB1.11224†



12" x 24" MTLB3.11224†



12" x 24" MTLB4.11224†



2" x 24" MTLB1.10224†



2" x 24" MTLB3.10224†




2" x 24" MTLB4.10224†

2" x 2" Mixed Mosaics (12" x 12" mounted sheets)



White MTLB1.10202



Grey MTLB3.10202



Copper MTLB4.10202



Schluter has created custom coordinating trim exclusively for the UltiMetal series. Please visit www.schluter.com to see this collection of metallic trim.



Sizes - (Available in all colors)

Nominal Size	Metric	Thickness (mm)
6" x 24"	147 x 597	10.5
12" x 12"	297 x 297	10.5
12" x 24"	297 x 597	10.5
24" x 24"	597 x 597	10.5

Coordinating Trim

2" x 2" Mosaics*	297 x 297	10.5
2" x 24" Listello†	47 x 597	10.5
12" x 24" Listello†	297 x 597	10.5

*12" x 12" mounted sheet size is 11-11/16" x 11-11/16"

†Alignment is not possible therefore pieces should not be paired/stacked

Recommended Usage

UltiMetal field tile is recommended for interior floors, walls and countertops and exterior walls in both residential and commercial applications. The 12" x 24" listello is recommended for interior walls only. The 2" x 24" listello and 2" x 2" mosaics are recommended for interior walls and light-duty interior floors.

Care and Maintenance

Regular cleaning is the best way to keep UltiMetal tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance

of Crossville products is available at www.crossvilleinc.com.


Product Performance

Water Absorption	<0.10%	ASTM C373
Breaking Strength	>500 lbf.	ASTM C648
Bond Strength	>200 psi	ASTM C482
Frost Resistance	Resistant	ASTM C1026
Chemical Resistance	Unaffected	ASTM C650
Scratch Hardness	6	MOH's Scale
Visible Abrasion	ASTM C1027	
	MTL04	Class 2
	MTL02, MTL03, MTL05	Class 3
	MTL01	Class 4
Coefficient of Friction		
COF-Dry	>0.8	ASTM C1028
COF-Wet	>0.7	ASTM C1028

Shade & Texture Index

UltiMetal has a shade variation of V2

V2 = Uniform Appearance



V1-Uniform Appearance
V2-Slight Variation
V3-Moderate Variation
V4-Substantial Variation



** Listellos Globally Sourced



Products featured in photo above:
Floor: MTL05 Black 12" x 24", 24" x 24"
Fireplace surround: MTLB3 Grey Mixed Mosaics MTLB1 White Mixed Mosaics