




Pompeii

PORCELAIN STONE®

 CROSSVILLE®  
ELEVATE YOUR SPACE

# Pompeii



VS50 Forum Stone



VS53 Etruscan Clay



VS52 Antico Silver



VS54 Apollo Bronze



VS51 Pietra Vecchia



VS55 Lava Brown



Product featured in photo above:  
Apollo Bronze VS54 6"x 6", 12"x 12", 18"x 18"

## Sizes (Available in all colors)

Nominal Size	Actual Size (in)	Thickness (in)
6 x 6	5-3/4 x 5-3/4	5/16
12 x 12	11-3/4 x 11-3/4	5/16
18 x 18	17-3/4 x 17-3/4	3/8

## Trim (Available in all colors)

4 x 12 Single Bullnose	3-3/4 x 11-3/4	5/16
6 x 12 Cove Base	5-3/4 x 11-3/4	5/16



4" x 12" Single Bullnose



6" x 12"  
Cove Base

## Product Performance

Breaking Strength	>350 lbf.	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.10%	ASTM C373
Scratch Hardness	8	MOH's Scale

## Coefficient of Friction

Dry	>0.8	ASTM C1028
Wet	>0.6	ASTM C1028

## Recommended Use

Pompeii is recommended for interior floors and walls and exterior walls. Pompeii is not recommended for exterior horizontal surfaces or exterior paving.

## Care and Maintenance

Regular cleaning is the best way to keep Pompeii tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville products is available at [www.crossvilleinc.com](http://www.crossvilleinc.com).

## Shade & Texture Index

Pompeii VS50, VS52 have a shade variation of V2.

Pompeii VS51, VS53, VS54, VS55 have a shade variation of V3.



V1



V2



V3



V4

V1=Uniform Appearance  
V2=Slight Variation  
V3=Moderate Variation  
V4=Substantial Variation

